

GT SONIC-D SERIES ULTRASONIC CLEANER



Features:

- 1.Normal and soft power control to resolve the cleaning blind spot .
- 2.Degas function for improve the cleaning effect.
- 3.Time Setting:1-99minutes adjustable.
- 4.Heating: 0-80℃ temperature adjustable
- 5.User-friendly and clear panel
- 6.Memory function
- 7.LED display for temperature and timer
- 8.High-performance transducer
- 9.Patent products

Application:

D series ultrasonic cleaner are used widely in Laboratory,Medical/Dental,Gem/Jewelry, Optics,Electronics, Automotive,Industry,Pharmaceutical to provide simple,effective results for cleaning objects.

Degas function especially suitable for “beyond cleaning” applications such as sample preparation, which includes degassing ,mixing, homogenization, dissolving ,cell lysing and dispersion of particles.

Specification:

Model	Tank size	Unit size	Volum e	Ultrasoni c power	Ultrasonic frequency	Heating power	Timer	Heating temperature
	L×W×H(mm)	L×W×H(mm)	(L)	Normal (W)	(kHz)	(W)	(MIN)	(℃)
GT SONIC-D2	150×140×100	190×170×220	2	50	40	100	1-99	0-80
GT SONIC-D3	240×140×100	270×170×240	3	100		100	1-99	0-80
GT SONIC-D6	300×155×150	330×180×310	6	150		300	1-99	0-80
GT SONIC-D9	300×240×150	330×270×310	9	200		300	1-99	0-80
GT SONIC-D13	330×300×150	360×330×310	13	300		400	1-99	0-80
GT SONIC-D20	500×300×150	550×330×310	20	400		500	1-99	0-80
GT SONIC-D27	500×300×200	550×330×360	27	500		500	1-99	0-80